

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025794 A1

(51) International Patent Classification:
5/0687

H01S 5/14,

(74) Agent: BARTH, Daniel; Agilent Technologies Deutsch-
land GmbH, Patentabteilung, Herrenbergerstr. 130, 71034
Böblingen (DE).

(21) International Application Number:

PCT/EP2002/010286

(22) International Filing Date:

13 September 2002 (13.09.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): AGI-
LENT TECHNOLOGIES, INC. [US/US]; 395 Page
Mill Road, Palo Alto, CA 94306 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): STEFFENS, Wolf
[DE/DE]; Schwarzwaldstrasse 84, 71083 Herrenberg
(DE). KALLMANN, Ulrich [DE/DE]; Haaggasse 17,
72070 Tuebingen (DE). HAEUSSLER, Ralf [DE/DE];
Richard-Wagner-Strasse 37, 71116 Gärtringen (DE).
NEBENDAHL, Bernd [DE/DE]; Ziehrerweg 1, 71254
Ditzingen (DE). JENSEN, Thomas [DE/DE]; Germanen-
strasse 20, 70563 Stuttgart (DE). MUELLER, Emmerich
[DE/DE]; Finkenweg 7, 71134 Aidlingen (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: CONTROL OF LASER TUNING VELOCITY



(57) Abstract: The present invention relates to an apparatus and to a method of manipulating a laser source (2), the method comprising the steps of: analyzing an optical signal (3, 4, 5) generated by the laser source (2), evaluating on the basis of the analysis an actual indicator corresponding with an actual value of a tuning velocity of the laser source (2), comparing the actual indicator with a desired indicator corresponding with a desired value of the tuning velocity to detect a deviation of the actual value of the tuning velocity from the desired value of the tuning velocity, and compensating the deviation if any by manipulating at least one parameter influencing the signal (3, 4, 5) of the laser source (2).

BEST AVAILABLE COPY

WO 2004/025794 A1

WO 2004/025794 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/025794

PCT/EP2002/010286

CONTROL OF LASER TUNING VELOCITY

BACKGROUND OF THE INVENTION

- The present invention relates to manipulating a laser source, in particular to manipulating an optical signal leaving the laser source, more particular to manipulating an optical signal leaving a tunable laser source (TLS) swept in frequency.

SUMMARY OF THE INVENTION

It is an object of the invention to provide improved manipulation of a laser source. The object is solved by the independent claims.

- 10 When tuning or sweeping the frequency of a TLS it often happens that the tuning velocity of the TLS is not linear. An advantage of an embodiment of the present invention is the possibility of compensating such non-linearity in the sweeping velocity when sweeping the frequency of the TLS.

- Another advantage of embodiments of the present invention is that it is possible to compensate jitter on a signal of a certain frequency of the TLS, i.e. small but fast oscillations of the signal of the TLS about the desired frequency. Since jitter can also be understood as a tuning velocity, although undesired, jitter can be compensated, also. This can be done for example by interferometrically analyzing the signal generated by the TLS. If any beat frequency, i.e. a frequency generated by an interferometer in which light is split and recombined again after propagating two different path length, can be detected in the superimposed signal of the interferometer then there is jitter, i.e. a small and fast but undesired tuning velocity, on the signal which can be compensated until there is no jitter on the signal any more, i.e. the tuning velocity is zero.

In an embodiment of the present invention the compensation is realized by measuring an actual value of an indicator of the sweeping velocity, preferably by using a frequency or wavelength reference unit (WRU), by comparing the

measured value with a desired value, preferably by using a deviation detector, and by compensating a deviation when a deviation was detected, preferably by using a phase controller influencing the signal of the laser source. The indicator can also be the tuning velocity itself. The WRU can be embodied by any kind of appropriate wavemeter and preferably as disclosed in any one of the following patent applications: EP-A-1099943, EP-A-1221599, or EP-A-0875743, the teaching thereof shall be incorporated herein by reference.

Furthermore, it is advantageous to generate the desired value by an electrical signal generator which can be forced by an appropriate control unit to generate as an indicator of the desired tuning velocity a frequency corresponding to the desired tuning velocity. Advantageously, this frequency can then be compared with a frequency measured by an interferometric WRU and a possible detection of a deviation is then be used to influence the optical signal created by the TLS.

The TLS can be influenced by using a phase controller introduced into the path of the laser in the TLS. Preferably, the phase controller comprises a fast phase controller to react on fast but small deviations and a slow phase controller to react on slow but large deviations. The fast phase controller can comprise an electro-optical modulator (EOM). The slow phase controller can comprise an actuator, which can comprise a piezo-electric element.

Possible application fields of embodiments of the present invention are measurement setups for measuring an optical property of a device under test using a TLS.

Other preferred embodiments are shown by the dependent claims.

It is clear that the invention can be partly embodied or supported by one or more suitable software programs, which can be stored on or otherwise provided by any kind of data carrier, and which might be executed in or by any suitable data processing unit.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and many of the attendant advantages of the present invention

will be readily appreciated and become better understood by-reference to the following detailed description when considering in connection with the accompanied drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present invention. Features that are substantially or functionally equal or similar will be referred to with the same reference sign(s).

Fig. 1 and 2 show schematic illustrations of embodiments of the present invention.

DETAILED DESCRIPTION PREFERRED EMBODIMENTS OF THE INVENTION

Referring now in greater detail to the drawings, Fig. 1 shows a schematic illustration of an apparatus for compensating a deviation of an optical signal compared to a desired value, e.g. for compensating a non-linearity in a sweeping velocity of a TLS 2, according to an embodiment of the present invention.

In the specific embodiment of the TLS 2 as shown herein, the TLS 2 provides as output at least one of laser beams 3, 4, 5 and comprises a laser cavity 6. The laser cavity 6 comprises a lasing chip 8 and a cavity end element 10 providing a path 12 for the laser beam 12a within the cavity 6. In the path 12 there is introduced a movable tuning element 14 to tune the TLS 2. In this embodiment the TLS 2 is tuned with a tuning velocity of e.g. 100GHz/s. A lens 16 in the path 12 adjacent to the chip 8 is provided to focus the laser beam 12a onto the chip 8. A lens 18 adjacent to the chip 8 opposite to the lens 16 is provided to focus the resulting laser beam 3 of the TLS 2. A beam splitter 20 in the path 12 adjacent to the lens 16 is provided to provide the resulting laser beam 4 of the TLS 2.

Any other type of TLS as the specific embodiment of TLS 2 can be applied accordingly, as will be shown in the following.

An EOM 22 as a fast phase controller (FPC) in the path 12 adjacent to the

beam splitter 20 is provided as a fast phase control of the resulting beams 3, 4, 5 of the TLS 2. A piezo electric element 24 as a slow phase controller (SPC) in contact with the cavity end element 10 provides a slow phase control of the resulting beams 3, 4, 5 of the TLS 2. How to control the FPC 22 and the SPC 24 will be described below.

A part of beam 3 is provided to a connector 26. Alternatively, beams 3- 5 or parts of the other beams 4 and 5 or any other combination of beams 3-5 can be provided to the connector 26. The connector 26 provides beam 3 to a fiber 28. Fiber 28 is part of an interferometer 30 comprising two two-port couplers 32 and 34, a delay loop 36, a second fiber 38 and detectors 40 and 42 to detect the power of the light emitted by fibers 28 and 38. Alternatively, not shown three-port couplers can be used instead of the two-port couplers 32 and 34. Moreover, all kinds of interferometers can be used for the purpose of the present invention, e.g. Michelson-, Mach-Zehnder-, Fabry-Perot-, or Fizeau-interferometers.

A subtractor 44 is connected to the detectors 40 and 42 to subtract the signals detected by the detectors 40 and 42 from each other to provide a resulting signal 46. Resulting signal 46 is provided to a frequency deviation detection unit (FDDU) 48 comprising a memory 50 to store a dependency of the detected frequency detected by detectors 40 and 42 on the tuning velocity of TLS 2. FDDU 48 controls via a high pass filter (HP) 52 with the FPC 22 and via a low pass filter (LP) 54 with the SPC 24.

An inventive method according to the shown embodiment works as follows:

When tuning the TLS 2 it is generated a laser beam 3 with increasing optical frequency. A part of laser beam 3, e.g. 5 % of beam 3, is coupled to connector 26. Coupler 32 splits the signal of fiber 28 into two parts 56 and 58. These parts 56 and 58 interfere at coupler 34 and generate a signal of a certain frequency, which is an indicator or measure of the tuning rate of the TLS 2. Detector 40 detects a signal having this frequency. Detector 42 detects a signal having the same frequency. These two signals are subtracted by a subtractor

✱

44 to provide signal 46 to the FDDU 48 again having the same but amplitude shifted frequency. FDDU compares the frequency of signal 46 with the frequency stored in memory 50 for the above mentioned tuning velocity of TLS 2. When FDDU 48 detects a deviation of the tuning velocity from the desired
5 above mentioned tuning velocity it provides appropriate control signals to FPC 22 and to SPC 24 to compensate for the deviation until there is no deviation anymore, i.e. the measured tuning velocity is equal to the desired tuning velocity.

According to the above described method it is also possible to compensate
10 jitter on beams 3-5 of TLS 2.

Fig. 2 shows a schematic illustration of a preferred embodiment 48-2 of the FDDU 48. The FDDU 48-2 comprises an electrical signal generator 60 forced by a control unit 62 to generate a desired frequency 66 corresponding to the desired tuning velocity. The desired frequency 66 is phase shifted by a phase
15 shifter 64 to implement a fixed phase relation between the desired frequency 66 and the measured frequency 46 and then desired frequency 66 is compared with the measured frequency 46 measured by the interferometric WRU 30 by mixing the desired frequency 66 and the measured frequency 46 with a mixer 68. A possible detection of a deviation is then be used to influence the TLS 2
20 according to the above described method.

CLAIMS:

1. A method of manipulating a laser source (2), comprising the steps of:
analyzing an optical signal (3, 4, 5) generated by the laser source (2),
evaluating on the basis of the analysis an actual indicator corresponding
with an actual value of a tuning velocity of the laser source (2),
comparing the actual indicator (46) with a desired indicator (66)
corresponding with a desired value of the tuning velocity to detect a
deviation of the actual value of the tuning velocity from the desired value
of the tuning velocity, and
compensating the deviation, if any, by manipulating at least one
parameter influencing the signal (3, 4, 5) of the laser source (2).
2. The method of claim 1, further comprising the steps of:
analyzing the optical signal (3, 4, 5) by:
letting a first part (56) of the signal (3, 4, 5) interfere with a second part
(58) of the signal (3, 4, 5) resulting in a superimposed signal, with the first
part (56) being delayed with respect to the second part (58), and
detecting the power of the superimposed signal.
3. The method of claim 2, further comprising the steps of:
evaluating the actual indicator by:
measuring as the actual indicator a frequency (46) of oscillations of the
detected power.
4. The method of claim 3, further comprising the steps of:
supplying the desired indicator by using a stored dependency of
frequency of oscillations of a detected power of the signal on tuning
velocity.

5. The method of claims 3 or any one of the above claims, further comprising the steps of:

supplying the desired indicator (66) by generating as the desired indicator (66) a frequency (66) corresponding to the desired tuning velocity.
- 5 6. The method of claims 3 or any one of the above claims, further comprising the steps of:

comparing the actual indicator with a desired indicator (66) by mixing the actual indicator (46) with the desired indicator (66).
- 10 7. The method of claim 1 or any one of the above claims, further comprising the steps of:

compensating the deviation if any by manipulating as a parameter a length of a cavity (6) of the laser source (2).
8. The method of claim 7, further comprising the steps of:

15 compensating a fast deviation, if any, by electro-optically changing an optical path length of the cavity (6).
9. The method of claim 7 or any one of the above claims, further comprising the steps of:

compensating a slow deviation if any by mechanically changing an optical path length of the cavity (6).
- 20 10. A software program or product, preferably stored on a data carrier, for executing the method of claim 1 or any one of the above claims, when run on a data processing system such as a computer.
11. An apparatus for manipulating a laser source (2), comprising:

25 an analyzer (30, 48, 48-2) for analyzing an optical signal (3, 4, 5) generated by the laser source (2), evaluating on the basis of the analysis an actual indicator (46) corresponding with an actual value of a tuning

- velocity of the laser source (2), and comparing the actual indicator with a desired indicator (66) corresponding with a desired value of the tuning velocity to detect a deviation of the actual value of the tuning velocity from the desired value of the tuning velocity, and
- 5 a compensator (22, 24) connected to the analyzer (30, 48, 48-2) for compensating the deviation if any by manipulating at least one parameter influencing the signal (3, 4, 5) of the laser source (2).
12. The apparatus of claim 11,
- wherein the analyzer (30, 48, 48-2) further comprises:
- 10 an interferometer (30) for letting a first part (56) of the signal (3, 4, 5) interfere with a second part (58) of the signal (3, 4, 5) resulting in a superimposed signal, with the first part (56) being delayed with respect to the second part (58), and
- a detector (40, 42) for detecting the power of the superimposed signal.
- 15 13. The apparatus of claim 12,
- wherein the analyzer (30, 48, 48-2) further comprises:
- a frequency deviation detection unit (48, 48-2) connected to the detector (40, 42) for measuring as the actual indicator a frequency (46) of oscillations of the detected power.
- 20 14. The apparatus of claim 13,
- wherein the analyzer (30, 48, 48-2) further comprises:
- a memory (50) for storing and supplying a dependency of frequency of oscillations of a detected power of the signal on tuning velocity to supply the desired indicator to the analyzer (30, 48, 48-2).
- 25 15. The apparatus of claims 13 or any one of the above claims,

wherein the analyzer (30, 48, 48-2) further comprises:

an electrical signal generator (60) for supplying the desired indicator (66) to the analyzer (30, 48, 48-2) by generating as the desired indicator (66) a frequency corresponding to the desired tuning velocity.

- 5 16. The apparatus of claims 13 or any one of the above claims,

wherein the analyzer (30, 48, 48-2) further comprises:

a mixer (68) for comparing the actual indicator (46) with a desired indicator (66) by mixing the actual indicator (46) with the desired indicator (66).

- 10 17. The apparatus of claim 11 or any one of the above claims, further comprising:

wherein the compensator (22, 24) further comprises:

a manipulator (22, 24) for manipulating as a parameter a length of a cavity (6) of the laser source (2), the manipulator (22, 24) being controlled
15 by the analyzer (30, 48, 48-2).


18. The apparatus of claim 17,

the manipulator (22, 24) further comprising:

an electro-optical modulator (22) in the path of the beam in the cavity (6) for compensating a fast deviation if any by electro-optically changing an
20 optical path length of the cavity (6).

19. The apparatus of claim 17 or any one of the above claims, further comprising:

a piezo-electric element (24) acting on an cavity end element (10) of the cavity (6) for compensating a slow deviation if any by mechanically
25 changing an optical path length of the cavity (6).






Fig. 2

INTERNATIONAL SEARCH REPORT

 Internati Application No
 PCT/EP 02/10286

 A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 H01S5/14 H01S5/0687

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 479 118 A (DORNIER GMBH) 8 April 1992 (1992-04-08)	1,2, 10-12
Y	column 3, line 22 -column 4, line 6; figure 1	7-9, 17-19
X	DE 44 29 748 A (FAGOR S COOP LTDA) 16 March 1995 (1995-03-16)	1,2, 10-12
Y	column 3, line 57 -column 4, line 12; figure 1 column 4, line 64 -column 5, line 5; figure 4	7-9, 17-19
Y	EP 1 220 389 A (AGILENT TECHNOLOGIES INC A DEL) 3 July 2002 (2002-07-03) column 4, line 50 -column 5, line 9; figure 3	7-9, 17-19
	----- -/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

& document member of the same patent family

Date of the actual completion of the international search

13 May 2003

Date of mailing of the international search report

22/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Jobst, B

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 02/10286

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 426 496 B1 (CHILDERS BROOKS A ET AL) 30 July 2002 (2002-07-30) column 4, line 18-37 -----	1-19
A	WO 00 49689 A (CHAPMAN WILLIAM B ;NEW FOCUS INC (US); GREEN EVAN D H (US); JENQ M) 24 August 2000 (2000-08-24) the whole document -----	7-9, 17-19

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 02/10286

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0479118	A	08-04-1992	DE 4031372 A1	09-04-1992
			EP 0479118 A2	08-04-1992
DE 4429748	A	16-03-1995	ES 2079282 A2	01-01-1996
			DE 4429748 A1	16-03-1995
EP 1220389	A	03-07-2002	EP 1220389 A1	03-07-2002
			DE 60100162 D1	08-05-2003
			JP 2003110177 A	11-04-2003
US 6426496	B1	30-07-2002	AU 7994100 A	04-03-2002
			WO 0216896 A1	28-02-2002
WO 0049689	A	24-08-2000	US 6108355 A	22-08-2000
			US 6282215 B1	28-08-2001
			AU 3859000 A	04-09-2000
			AU 6432399 A	08-05-2000
			EP 1153463 A1	14-11-2001
			EP 1129513 A1	05-09-2001
			JP 2002528902 T	03-09-2002
			WO 0049689 A1	24-08-2000
			WO 0024095 A1	27-04-2000
			US 6526071 B1	25-02-2003

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.